

No Lesen : PM072601
Licence No :

LESEN PENSIJILAN BARANGAN

Product Certification Licence



SIRIM QAS International Sdn. Bhd. dengan ini menganugerahkan kepada
SIRIM QAS International Sdn. Bhd. hereby grants to


MUI FATT MARKETING SDN. BHD.
LOT 11793
JALAN PENGKALAN NELAYAN
TELOK GONG
42000
SELANGOR, MALAYSIA

Lesen untuk menggunakan Tanda Pensijilan di atas barangan
a licence to use the Certification Mark on

GLASS REINFORCED PLASTICS OPEN BAR GRATINGS

Please refer to detail in the SCHEDULE

sebagai mematuhi keperluan
as complying with
BS 4592 : PART 4 : 1992



Khalidah Mustafa

Khalidah Mustafa
Pengarah Urusan
Managing Director
SIRIM QAS International Sdn. Bhd.

SIRIM QAS International Sdn. Bhd.
(No. Syarikat 410334-X)
1, Persiaran Dato' Menteri
Seksyen 2, Peti Surat 7035
40700 Shah Alam
Selangor Darul Ehsan
MALAYSIA.

Tel : 60-3-55446400
Faks : 60-3-55446466

<http://www.sirim.my>
<http://www.malaysian-certified.my>

Tarikh Mula Pensijilan : 16 November 2007
Certified Since
Sah Sehingga : 16 November 2015
Valid Until

Tarikh Dikeluarkan : 17 September 2014
Issue Date
No Siri : 013381
Serial No

Lesen ini dianugerahkan tertakluk kepada syarat-syarat Perjanjian Pensijilan Barangan SIRIM QAS International Sdn. Bhd.
This Licence is granted subject to the provisions of the Product Certification Agreement of SIRIM QAS International Sdn. Bhd.

SCHEDULE

MUI FATT MARKETING SDN. BHD.



SIRIM

Brand : MUIGRATE
Model : LIGHT DUTY (MAX. EFFECTIVE SPAN : 1000MM)
Rating : 14.7MM X 24.5MM X 5MM (MAX. PITCH : 152MM X MAX. CLEAR DISTANCE
BETWEEN LOAD BEARING BAR : 23.5MM)

WALKWAY, FLOORING AND TREADS

Model : HEAVY DUTY (MAX. EFFECTIVE SPAN : 800MM)
Rating : 14.7MM X 24.5MM X 5MM (MAX. PITCH : 152MM X MAX. CLEAR DISTANCE
BETWEEN LOAD BEARING BAR : 23.5MM)

WALKWAY AND FLOORING

Model : GENERAL DUTY (MAX. EFFECTIVE SPAN : 900MM)
Rating : 14.7MM X 24.5MM X 5MM (MAX. PITCH : 152MM X MAX. CLEAR DISTANCE
BETWEEN LOAD BEARING BAR : 23.5MM)

WALKWAY AND FLOORING

Model : LIGHT DUTY (MAX. EFFECTIVE SPAN : 1400MM)
Rating : 15.6MM X 37MM X 5.6MM (MAX. PITCH : 152MM X MAX. CLEAR DISTANCE
BETWEEN LOAD BEARING BAR : 23.5MM)

WALKWAY AND FLOORING

Model : LIGHT DUTY (MAX. EFFECTIVE SPAN : 1000MM)
Rating : 15.6MM X 37MM X 5.6MM (MAX. PITCH : 152MM X MAX. CLEAR DISTANCE
BETWEEN LOAD BEARING BAR : 23.5MM)

TREADS

Model : GENERAL DUTY (MAX. EFFECTIVE SPAN : 1200MM)
Rating : 15.6MM X 37MM X 5.6MM (MAX. PITCH : 152MM X MAX. CLEAR DISTANCE
BETWEEN LOAD BEARING BAR : 23.5MM)

WALKWAY AND FLOORING

Model : HEAVY DUTY (MAX. EFFECTIVE SPAN : 1100MM)
Rating : 15.6MM X 37MM X 5.6MM (MAX. PITCH : 152MM X MAX. CLEAR DISTANCE
BETWEEN LOAD BEARING BAR : 23.5MM)

WALKWAY AND FLOORING

End of page